



**nitamericas**  
INCORPORATED

# HotShot 1700 cc

The Hotshot cc series from nit Americas incorporated:  
The family of ruggedized, compact highspeed camera systems.

## HotShot 1700 cc Features:

- CMOS Sensor : 1696 X 1710  
— all Active Pixels
- Reliable
- Easy-to-Use
- Bit Depth : 10-bit
- Electronic Shutter :  
OPEN to 2 $\mu$ sec
- Multiple Trigger Modes
- Synchronization: Internal  
and external sync recording
- Interface : Gigabit Ethernet
- Lens Mount : C-Mount,  
F-Mount with Adapter,  
AFG Mount available
- Compact Housing
- Ruggedized : Sealed camera  
core, uses no fans.
- Optional: LabView Driver



**T**he HotShot line of high-speed digital video cameras provides the user with rates, high resolutions and long record times... all in an extremely compact package!

The extremely reliable HotShot 1700 cc records brilliant color images or crisp monochrome images at 500 fps with resolutions up to 1696 x 1710 pixels.

The HotShot 1700 cc is a versatile, easy-to-use camera system, that provides affordably priced high-speed video solutions to a broad array of users. Camera applications include: biomechanics, general research and test, machine design, production line maintenance, packaging and many, many more!

When it comes to reliable, high-quality, high-speed camera systems, make the proven choice with nit Americas and you'll see the visible difference!

# HotShot 1700 cc

## Frame Rate/Resolution Table

HotShot 1700 cc		
Max Res (pixels)	1696 X 1710	
Optical Format	19.27 mm	
fps @ Max Res	500	
Gpix/ sec @ Max Res	1.45	
	Mono	Color
ISO Rating	2,000	500
Memory Options	2GB, 4GB, 8GB, 16GB	
Max fps	100,000	

Imaging Formats	fps @ Format
1696 x 1710	500
1440 x 1074	1,000
1200 x 810	1,500
1056 x 702	2,000
800 x 590	3,000
736 x 474	4,000
608 x 438	5,000
544 x 394	6,000
352 x 322	10,000
224 x 206	20,000
224 x 126	30,000

\*Note: Recording Time Depends on Memory Configuration, Resolution, Frame and Image Bit Depth.

Recording Time (seconds) = [ (Memory Configuration x 1024 x 1,000,000) / (Frames/Second) ]

Resolution/Frame (Bytes) = (Horizontal pixels X Vertical Pixels X Bit Depth/8)

### HotShot cc High Speed Camera Systems also Feature:

- Adjustable Frame Rates
- Fast Gig-E Interface
- Continuous Live Video Output
- Interface - Gigabit Ethernet
- Memory Segmentation
- Remote Control via PC
- Internal and External Sync Recording
- Trigger Switch - TTL, switch, open collector, rising or falling edge, on image content variation
- Lens Mount C-mount, F-Mount with adapter, AFG Mount available
- Optional -Lab View Driver
- Power 12 VDC/12 W
- Compact, Rugged Design - 1.1kg 145W x 95H x 78.5D(mm)
- Intuitive Capture and Control software
- Analysis Software for 2D tracking of velocity, acceleration and displacement.

Please Note: Specification described above are preliminary and subject to change.



Contact Us in the Americas:  
 nac Image Technology  
 543 Country Club Drive, # B-534  
 Simi Valley, CA 93065  
 Tel: (800) 969-2711  
 E-mail: sales@nacinc.com

Contact Us in Europe:  
 nac Deutschland GmbH  
 Hedelfingerstr. 54-70  
 70327 Stuttgart, Germany  
 Tel: +49(0)711 2201 885  
 E-mail: rwestphal@nacinc.de

Contact Us in Asia:  
 nac Image Technology Inc.  
 2-11-3 Kita-Aoama, Minato-ku  
 Tokyo 107-0061 Japan  
 Tel: +81 3 3796 7903  
 Email: nacinternational@camnac.co.jp